

Output voltage (V)	Output current (A)	Mains (VAC)	Input current (A)	Mains protection (A)	Case with air pump	Case without air pump	Type	Charging time / Battery capacity (Ah max.)					Weight (Kg)	
								with air pump		without air pump		gel	with air pump	without air pump
								6h	8h	8h	10h	10h		
24	60	230	8,7	10	FF170	FF130	FLEXIS 24E60	308	462	423	571	316	15	13
	100	230	14,1	16	FF170	FF130	FLEXIS 24E100	513	769	704	952	526	15	13
	100	3 x 400	4,9	6	FF170	FF130	FLEXIS 24D100	513	769	704	952	526	16	14
	200	3 x 400	9,8	10	FF250	FF250	FLEXIS 24D200	1026	1538	1408	1905	1053	26	25
48	50	230	14,1	16	FF170	FF130	FLEXIS 48E50	256	385	352	476	263	15	13
	50	3 x 400	4,9	6	FF170	FF130	FLEXIS 48D50	256	385	352	476	263	16	14
	100	3 x 400	8,0	10	FF170	FF130	FLEXIS 48D100	469	704	644	871	482	20	18
	150	3 x 400	12,9	16	FF250	FF250	FLEXIS 48D150	726	1088	996	1348	745	28	27
	200	3 x 400	16,0	20	FF250	FF250	FLEXIS 48D200	938	1408	1289	1743	963	31	30
80*	25	230	14,1	16	FF250	FF130	FLEXIS 80E25	128	192	176	238	132	16	13
	25	3 x 400	4,9	6	FF250	FF130	FLEXIS 80D25	128	192	176	238	132	17	14
	50	3 x 400	8,0	10	FF250	FF130	FLEXIS 80D50	256	385	352	476	263	20	17
	75	3 x 400	12,9	16	FF330	FF250	FLEXIS 80D75	385	577	528	714	395	30	26
	100	3 x 400	16,0	20	FF330	FF250	FLEXIS 80D100	513	769	704	952	526	32	28
	125	3 x 400	20,9	25	FF550	FF330	FLEXIS 80D125	641	962	880	1190	658	42	37
	150	3 x 400	24,0	32	FF550	FF330	FLEXIS 80D150	769	1154	1056	1429	789	45	40
	175	3 x 400	28,9	32	FF550	FF550	FLEXIS 80D175	897	1346	1232	1667	921	54	49
	200	3 x 400	32,0	40	FF550	FF550	FLEXIS 80D200	1026	1538	1408	1905	1053	56	52
	225	3 x 400	36,9	40	FF720	FF720	FLEXIS 80D225	1154	1731	1585	2143	1184	65	63

* Intended also for 96V and 110V Batteries

Other types on request. Battery capacity values in the table according to IULa dU charging curve.



www.axima.cz

AXIMA, spol. s r.o., Vídeňská 125, Brno CZ 619 00

tel.: +420 547 424 011 • fax: +420 547 424 030 • e-mail: acdc@axima.cz