

Output voltage (V)	Output current (A)	Mains (VAC)	Input current (A)	Mains protection (A)	Case	Type	Charging time / Battery capacity (Ah max.)				Weight (Kg)
							Lead acid batteries		Gel batteries		
							8h	10h	10h	12h	
24	60	230	8,7	10	FF130	FORTIS 24E60	423	571	316	420	13
	100	230	14,1	16	FF130	FORTIS 24E100	704	952	526	699	13
	100	3 x 400	4,9	6	FF130	FORTIS 24D100	704	952	526	699	14
	200	3 x 400	9,8	10	FF250	FORTIS 24D200	1408	1905	1053	1399	25
48	50	230	14,1	16	FF130	FORTIS 48E50	352	476	263	350	13
	50	3 x 400	4,9	6	FF130	FORTIS 48D50	352	476	263	350	14
	100	3 x 400	8,0	10	FF130	FORTIS 48D100	644	871	482	640	18
	150	3 x 400	12,9	16	FF250	FORTIS 48D150	996	1348	745	990	27
	200	3 x 400	16,0	20	FF250	FORTIS 48D200	1289	1743	963	1280	30
80*	25	230	14,1	16	FF130	FORTIS 80E25	176	238	132	175	13
	25	3 x 400	4,9	6	FF130	FORTIS 80D25	176	238	132	175	14
	50	3 x 400	8,0	10	FF130	FORTIS 80D50	352	476	263	350	17
	75	3 x 400	12,9	16	FF250	FORTIS 80D75	528	714	395	524	26
	100	3 x 400	16,0	20	FF250	FORTIS 80D100	704	952	526	699	28
	125	3 x 400	20,9	25	FF330	FORTIS 80D125	880	1190	658	874	37
	150	3 x 400	24,0	32	FF330	FORTIS 80D150	1056	1429	789	1049	40
	175	3 x 400	28,9	32	FF550	FORTIS 80D175	1232	1667	921	1224	49
	200	3 x 400	32,0	40	FF550	FORTIS 80D200	1408	1905	1053	1399	52
225	3 x 400	36,9	40	FF720	FORTIS 80D225	1585	2143	1184	1573	63	

* Intended also for 96V and 110V Batteries. Other types on request.



www.axima.cz

AXIMA, spol. s r.o., Vídeňská 125, Brno CZ 619 00

tel.: +420 547 424 011 • fax: +420 547 424 030 • e-mail: acdc@axima.cz